



**ITEM 1: THIMBLE CLEVIS**

C/W PIN AND HUMPBACK SPLIT PIN  
REFER STD DRG No. S01-01-04-03

ITEM NUMBER : 6767

**ITEM 2: 22kV POLYMER SUSPENSION INSULATOR**

DRY ARCING DISTANCE (MM)	285	DESIGN TENSION STRENGTH (kN)	107
CREEPAGE DISTANCE (MM)	645	ROUTINE TEST LOAD (kN)	37
LOW FREQUENCY FLASHOVER:		TENSILE RATING (kN)	70
DRY (kV)	130	DESIGN TORSION RATING (Nm)	67
WET (kV)	114	NET WEIGHT (kg)	1.24

MATERIAL:  
SHEDS - RUBBER (EPDM AND/OR SILICONE)  
METAL PARTS - FERROUS HOT DIPPED GALVANISED

ITEM NUMBER : 292656

**ITEM 3: TONGUE HOOK, REF 70TH**

COMPLIANT WITH AS 1154.1

ITEM NUMBER : 292680

ISOMETRIC  
N.T.S.

4	UPDATED AS REFERENCE ITEM 3.	A.N.	JUL'21	C.C.C.	B.V.
3	UP DATED TO 3D	C.C.	NOV'19	B.V.	B.V.
2	TITLEBLOCK & DRAWING NUMBERS FORMATTED	K.T.	DEC'18	C.C.	C.C.
1	DIMENSIONS ADDED	J.C.	FEB'08	A.T.	S.C.

NO	DESCRIPTION	DRN	DATE	CKD	APPD
AMENDMENTS					



DES	A.TICE	POWER STANDARD DRAWING		
DRN	R.INNES	LINE HARDWARE		
CKD	-	70kN SUSPENSION INSULATOR		
APPD	F.ROBSON	22kV & ASSOCIATED HARDWARE		
SCALE	N.T.S.	A3	DRAWING NUMBER	S01-01-03-09
ISSUED	APRIL 1999			
ALL DIM. IN mm				
DRAFTING STANDARD TO A.S.1100		CAD PRODUCT - DO NOT AMEND MANUALLY		AMDT