

DETAIL OF SLEEVE

95sq.mm SLEEVE SHOWN.

TABLE 1: ITEM DETAILS

ITEM	CONDUCTOR C.S.A	RATED TENSION	HEX. DIE A/F	ITEM
REF.	(sq.mm)	(kN)	(mm)	NUMBER
1	95	16.8	21.5	229039
2	150	7	21.5	415590

NOTES:

- CABLE INSULATION TO BE REMOVED TO DIMENSION SHOWN ON LINK AND FULLY INSERTED INTO LINK BEFORE COMPRESSION.
- 2. JOINTS TO BE MADE WITH INDIVIDUAL CORE JOINTS STAGGERED MIN 150mm.
- 4. LINK TO HAVE EMBOSSED ON THE INSULATION:
 - STRIPPING LENGTH,
 - COMPRESSION DIE SIZE A/F,
 - NUMBER, LOCATION AND SEQUENCE OF COMPRESSIONS.
- 5. USE TERMINATION LUG COMPRESSION 504381 BIMETAL INSULATED. S02-01-02-22
- TO COMPLY WITH PWC SPECIFICATION STSP 05-013.

	AMENDMENTS								
	VO	DESCRIPTION	DRN	DATE	CKD	APPD			
	3	TABLE AND NOTE 4 AMENDED	K.T.	NOV'99	G.H.	F.R.			
	4	AMENDED NOTES	K.T.	FEB'08	B.C.	S.C.			
1	5	150sqmm VERSION ADDED	K.T.	MAR'12	B.C.	S.C.			
	6	TITLEBLOCK & DRAWING NUMBER FORMATTED	K.T.	DEC'19	0.0	C.C.			
1	1	REFORMATTED TABLE & TEXT. CHANGED ITEM 2 A/F. REMOVED COLOURS & NOTE 3	A.N.	AUG'21	A.N.	B.V.			
1	8	AMENDED ITEM 3. ADDED NOTE 5.	P.BH.	NOV'22	B.V.	B.C.			
	9	REMOVED ROW 2 ON THE TABLE. ADDED NOTE 5.	J.R.	SEP'24	J.R.	B.B.			



DES	A.B.	POWER STANDARD DRAWING						
DRN	A.DAVIS							
CKD	R. INNES	LV AERIAL BUNDLED CABLE						
APPD	F.ROBSON	LINK - COMPRESSION						
SCALE	N.T.S.							
ISSUED	MAY'98	A 7	DRAWING	COA OA OO 47				
ALL DI	M. IN mm	A3	NUMBER	S04-01-02-17				
DRAFTING STANDARD TO A.S.1100			CAD PRODUCT	- DO NOT AMEND MANUALLY	AMDT			