



OVERALL DIMENSIONS		
LENGTH	WIDTH	HEIGHT
686mm	67mm	* 171mm

* HEIGHT INCLUDES BUSBAR CLAMPS AND PHASE SHIELDS.

NOTES

1. BASE MATERIAL TO BE MOULDED PLASTIC.
2. BUSBAR MATERIAL TO BE ALUMINIUM.
3. VOLTAGE RATING TO BE 500V.
4. MAXIMUM CURRENT TO BE 400A.
5. FUSE CARTRIDGES TO BE DIN TYPE (REFER DRG. S2-1-4-10).

APPLICATION

NOT TO BE USED IN NEW PACKAGE SUBSTATIONS!
 FOR USE IN FUSED LV DISTRIBUTION PILLARS AND
 EXISTING PACKAGE SUBSTATIONS WITH HAZEMEYER
 STRIPLE FUSE UNITS.

ITEM 1 - STRIPLE FUSE BASE
 Stock Code - 11890
 (HAZEMEYER CATALOGUE No. 3485E.1322.516)

10	OBSOLETE	A.N.	JUL '21	C.C.C.	B.V.
9	TITLEBLOCK & DRAWING NUMBER FORMATTED	K.T.	APR '19	C.C.	C.C.
8	ITEM NUMBER, STOCK CODE, CATALOGUE NUMBER AND APPLICATION AMENDED	G.McK	JAN '91	-	-
NO	DESCRIPTION	DRN	DATE	CKD	APPD
AMENDMENTS					



DES	-	POWER STANDARD DRAWING		
DRN	G.McK	FUSES & SWITCHGEAR FUSE BASE STRIPPLE FUSE - 500V - 400A		
CKD	N.STUBBS			
APPD	B.T.KENT			
SCALE	N.T.S.			
ISSUED	JAN '91	A3	DRAWING NUMBER	S02-01-04-11
ALL DIM.	IN mm			
DRAFTING STANDARD TO A.S.1100		CAD PRODUCT - DO NOT AMEND MANUALLY		AMDT