



**CLAMP STRAIN 4x95/4x150mm<sup>2</sup>**  
 (ITEM No. - 415585)

**NOTES**

1. ALL EXTRUDED MATERIALS TO BE UV STABILIZED
2. CLAMP TO BE FITTED WITH SEPARATING SPRINGS
3. ALL BOLTS TO HAVE CAPTIVE HEADS.
4. CORROSION PROTECTION TO BE HOT DIPPED GALVANIZING. WHEREBY COMPONENTS ARE TO BE EVEN AND FREE FROM LUMPS, AND BUILD- UP AND TRUE TO SHAPE AFTER GALVANIZING COMPONENTS WILL BE TESTED IN ACCORDANCE WITH AS 4680
5. ALL STRAIN CLAMPS TO COMPLY WITH AS3766 SECTION 2

2 TITLEBLOCK & DRAWING NUMBER FORMATTED 1 NOTE 5 ADDED. REDRAWN IN 3D ITEM CHANGED TO 4X95/4X150						K.T. J.C.	JAN'20 MAR'12	C.C. A.T.	C.C. S.C.	POWER STANDARD DRAWING		
										DES A.TAYLOR DRN J.COPPINS CKD A.TAYLOR APPD B.CHEUNG SCALE N.T.S. ISSUED MAR'12 ALL DIM. IN mm DRAFTING STANDARD TO A.S.1100		LINE HARDWARE LV-ABC CLAMP STRAIN
AMENDMENTS						CAD PRODUCT - DO NOT AMEND MANUALLY						AMDT

