



DETAIL OF SLEEVE
16sq.mm DULMISON TYPE

NOTES:

1. CABLE INSULATION TO BE REMOVED TO DIMENSION SHOWN ON LINK AND FULLY INSERTED INTO LINK BEFORE COMPRESSION.
2. JOINTS TO BE MADE WITH INDIVIDUAL CORE JOINTS STAGGERED MIN 150mm.
3. 3 CRIMPS 9mm WIDE EACH SIDE OF JOINT.
4. DIE UTILUX NO 38-140

3	LINK - COMPRESSION - NON TENSION 16sq.mm	70	16	289587	MJPB16E	MJPB16CG
2	LINK - COMPRESSION - NON TENSION 16-25sq.mm	70	16	288035	MJPB16E-25	MJPB25-16CG
1	LINK - COMPRESSION - NON TENSION 25sq.mm	70	16	288027	MJPB25	MJPB25CG
ITEM	DESCRIPTION	A(mm)	B(mm)	ITEM NUMBER	DULMISON PART NO	SICAME PART NO

3	OBSOLETE. REFORMATTED TEXT.	A.N.	JUL'21	C.C.C.	B.V.
2	TITLEBLOCK & DRAWING NUMBER FORMATTED	K.T.	DEC'18	C.C.	C.C.
1	LOGO CHANGED	C.C.	JAN'11	A.T.	S.C.
NO	DESCRIPTION	DRN	DATE	CKD	APPD
AMENDMENTS					



DES	A.BUTLER	POWER STANDARD DRAWING			
DRN	R. INNES	LINE HARDWARE LV SERVICE LINK COMPRESSION			
CKD	-				
APPD	F.ROBSON				
SCALE	2:1	A3	DRAWING NUMBER	S01-01-04-31	
ISSUED	JUN'98				
ALL DIM.	IN mm	CAD PRODUCT - DO NOT AMEND MANUALLY			
DRAFTING STANDARD TO A.S.1100				AMDT	