



**12.5C ROUND POLE SPECIFICATION:**

ITEM NUMBER 414254  
 LENGTH 12.5m  
 DIAMETER 323mm  
 WALL THICKNESS 4.7mm  
 ULTIMATE STRENGTH RATING: 16kN  
 EMBEDMENT DEPTH 2.1m  
 GROUND LEVEL PROTECTION SPRAY LENGTH 1.00m  
 0.5m ABOVE GROUND LEVEL  
 0.5m BELOW GROUND LEVEL

DISTANCE FROM TOP (mm)	HOLE DIAMETER (mm)									
	0°	45	90	120	135	180	225	240	270	315
120	26					26				
220			26						26	
320		26			26		26			26
720	26					26				
820			26						26	
920		26			26		26			26
950			M16						M16	
1320	26					26				
1400	M12			M16		M12				
1420			26						26	
1520		26			26		26			26
1850									M16	
1920	26					26				
2020			26						26	
2120		26			26		26			26
2300	M12		M16			M12			M16	
2520	26					26				
2750									M16	
2900	26					26				
3100	26					26				
3200	M12		M16			M12			M16	
3220			26						26	
3650									M16	
3720	26					26				
3800	M12									
3820			26						26	
4320	26					26				
4420			26						26	
5800	M12									
7900	M12		M12	M12					M12	M12
8900	M12		M12	M12					M12	M12
9800	M12		M12			M12			M12	
9900	TOP OF GROUND LEVEL PROTECTION									
10400	GROUND LEVEL									
10900	BOTTOM OF GROUND LEVEL PROTECTION									

NO	DESCRIPTION	DRN	DATE	CKD	APPD
<b>AMENDMENTS</b>					
3	OBSOLETE	A.N.	SEP'21	A.N.	B.V.
2	TITLEBLOCK & DRAWING NUMBER FORMATTED	K.T.	DEC'18	C.C.	C.C.
1	TABLE DETAILS AMENDED	A.T.	OCT'12	B.C.	S.C.
0	ISSUED FOR CONSTRUCTION	C.C.	SEP'11	A.T.	S.C.



DES	A.T.	POWER STANDARD DRAWING		
DRN	C.C.	<b>POLES          ROUND LINE 12.5C          BOLTED CONNECTIONS TYPE</b>		
CKD	A.T.			
APPD	S.C.			
SCALE	N.T.S.			
ISSUED	SEP'11	A3	DRAWING NUMBER	S01-01-01-27
ALL DIM.	IN mm			
DRAFTING STANDARD TO A.S.1100			CAD PRODUCT - DO NOT AMEND MANUALLY	

